

CUSTOMER FOCUS ON **LOSS CONTROL**

NUMBER 78

Felling Trees With A Chain Saw *Checklist for Field Use*

Personal Equipment

- Hard hat
- Eye/face protection
- Hearing protection
- Foot protection
- Tools (wedges, axes, etc.)
- Hand protection
- Leg protection
- First aid kit



Chain Saw

- Chain brake
- Throttle interlock
- Chain catcher
- Chain tension
- Muffler
- Chain saw kickback
- Chain sharpness, cutter shape, depth setting, and lubrication
- Handles and guards are tight
- No chain movement when engine is idling

Considerations Prior to Felling

- Determine hazards in the area
- Determine felling direction and tree lean
- Pick a clear retreat path
- Determine the proper hinge size to safely guide the tree in its fall.
- Always use proper felling methods

Work Practices

- Continuous pressure throttle
- Operate and adjust saw in accordance with the manufacturer's instructions
- Fuel saw 20 feet from sources of ignition
- Start saw 10 feet from fueling area
- Use proper starting methods
- Engage chain brake when starting
- Use correct hand position on handles
- Use proper footing/body position
- Clear the area prior to felling
- Do not cut above your head
- Use proper methods for:
 - Carrying the saw
 - Retreating with the saw
 - Moving with a running saw

This document is provided for information purposes only. It is not intended to be a substitute for individual legal counsel or advice on issues discussed within. Readers seeking resolution of specific legal issues or business concerns related to the captioned topic should consult their attorney and/or insurance representative.

Copyright © 1999 The Hartford Loss Control Department. All rights reserved.

